

CORIAN® ENDURA™

INTERIOR VERTICAL APPLICATIONS

Introduction

This fabrication bulletin addresses the basic design concepts for vertical applications of Corian® Endura™ high performance porcelain.

Overview

Typical backsplashes of less than 150 mm (6") are installed using typical techniques with 100% silicone adhesive. Larger applications will require additional considerations.

Due to the weight of Corian® Endura™ the use of 12-mm thick slabs is recommended for the majority of vertical applications with the exception of standard height backsplashes and the vertical portion of waterfall countertops.

Corian® Endura™ can be installed in a vertical position if expertly installed. Installations should only be designed and installed by individuals with demonstrated skills in large format porcelain slab installation. Due to the nature of the porcelain material and its weight (up to 337 lbs. (153 kg) for a 12 mm slab), there are technical and safety challenges to be considered when installing this type of material vertically, including – but not limited to – the below points:

- The structural strength of the wall/building should be checked to make sure it can withstand the structural load from the weight of the material,
- Appropriate know how, techniques and tools are required to safely secure pieces of porcelain material on a wall; these can include, but are not limited to, the use of specific adhesives and/or mortars, mechanical fasteners, anchoring systems, rail systems, etc.,
- Installers should always use safe methods to handle, move and position the material on the wall. Working with smaller pieces of material is one way to mitigate the risks associated with lifting and hanging heavy materials.

A. Panel Preparation

General cutting guidelines, guidance for cutouts and edge profile guidance apply. These are covered in *Corian® Endura™ Design* (K-30200).

B. Design

There should be a minimum 2 mm (³/₃₂") gap between slabs for interior vertical application. Fill this gap with grout suitable for porcelain. Avoid having large sections of slab on both sides of a cutout, adding seams if necessary.

There are both mechanical and adhesive methods of attaching slabs to a wall structure. Adhesive methods may require safety anchoring systems. The design must comply with any local building codes, which may require anchoring systems and may provide specific guidance for wet applications.

C. Installation Techniques

For mechanical hanging systems check with the vendor for guidance. Adhesive based installation methods are based on tile installation techniques and installations should be done by those familiar with these techniques. For safety anchors follow the guidance from the manufacturer for installation.

Safety is a key consideration due to the size and weight of slabs, which for a full trimmed 12-mm slab is 337 lb. (153 kg)

Slabs can be cut to smaller sizes for handling and safety.

D. Substrates

Use substrates specified for tile installation. The substrate and wall structure need to be able to accommodate the weight of the slab(s). There may be additional requirements (performance or building code) for wet applications.

E. Adhesives and Grout

Use adhesives designed for bonding to tile substrates (horizontal or vertical). These must meet ANSI A118.15HE or ISO 13007 C2TE S1. Consult with the adhesive manufacturer if adhesive does not list standards compliance.

Adhesive application is with a 3-mm tile trowel on the slab, and a 10-mm V-notch or 15-mm U-notch trowel on the substrate. Apply in a single and identical direction for both the slab and the substrate parallel to the short edge to aid in air removal when bringing the slab and substrate together.

CORIAN® ENDURA™ INTERIOR VERTICAL APPLICATIONS

F. Mechanical Support & Safety Attachments for Adhesive Attached Slabs

Installation of slabs in vertical applications must meet any local codes. Safety anchors are recommended for sizes over 60 cm (2 ft.) on longest side.

“Safety anchors”, “anchoring systems” or “safety withholding hooks” are safety features that restrain slab if adhesive bond fails. The manufacturer of these anchors will provide specific guidance for number and spacing of anchors. They also sell equipment to aid in installation.

A support in an edge slot in the bottom of a slab may be used to support the bottom of smaller sections (i.e. a countertop waterfall).

G. Additional Resources

For additional research on this topic, please review guidance from the Natural Stone Institute *Dimension Stone Design Manual - Chapter 15 Vertical Surfaces*. <http://pubs.naturalstoneinstitute.org/pub/2de67591-e0d4-196e-0566-f134cca32b13> This document is designed for stone, but many mechanical anchoring systems are similar.

Another resource is ANSI A108.19-2017 *American National Standard Specification for Interior Installation of Gauged Porcelain Tile Panels/Slabs by the Thin-bed Method Bonded with Dry Set Cement Mortar of Improved Modified Dry-Set Mortar*.

Equipment manufacturers for mechanical hanging systems and safety anchors also offer tools, anchors and guidance on use. The generic term for this category of product is “large format tile”.

H. Referenced Documents

Corian® Endura™ Design (K-30200)

Natural Stone Institute *Dimension Stone Design Manual - Chapter 15 Vertical Surfaces*

ANSI A108.19-2017 *American National Standard Specification 00for Interior Installation of Gauged Porcelain Tile Panels/Slabs by the Thin-bed Method Bonded with Dry Set Cement Mortar of Improved Modified Dry-Set Mortar*

PLEASE VISIT OUR WEB SITE: WWW.CORIANENDURA.COM OR CONTACT YOUR CORIAN® REPRESENTATIVE FOR MORE INFORMATION ABOUT CORIAN® ENDURA™.

This information is based on technical data that DuPont Specialty Products USA, LLC and its affiliates (“DuPont”) believe to be reliable, and is intended for use by persons having technical skill and at their own discretion and risk. DuPont cannot and does not warrant that this information is absolutely current or accurate, although every effort is made to ensure that it is kept as current and accurate as possible. Because conditions of use are outside DuPont’s control, DuPont makes no representations or warranties, express or implied, with respect to the information, or any part thereof, including any warranties of title, non-infringement of copyright or patent rights of others, merchantability, or fitness or suitability for any purpose and assumes no liability or responsibility for the accuracy, completeness, or usefulness of any information. This information should not be relied upon to create specifications, designs, or installation guidelines. The persons responsible for the use and handling of the product are responsible for ensuring the design, fabrication, or installation methods and process present no health or safety hazards. Do not attempt to perform specification, design, fabrication, or installation work without proper training or without the proper personal protection equipment. Nothing herein is to be taken as a license to operate under or a recommendation to infringe any patents. DuPont shall have no liability for the use of or results obtained from such information, whether or not based on DuPont’s negligence. DuPont shall not be liable for (i) any damages, including claims relating to the specification, design, fabrication, installation, or combination of this product with any other product(s), and (ii) special, direct, indirect or consequential damages. DuPont reserves the right to make changes to this information and to this disclaimer. DuPont encourages you to review this information and this disclaimer periodically for any updates or changes. Your continued access or use of this information shall be deemed your acceptance of this disclaimer and any changes and the reasonableness of these standards for notice of changes.

Corian®, the Corian® logo system, Endura™, and all trademarks and service marks denoted with ™, ® or ® are trademarks or registered trademarks of affiliates of DuPont de Nemours, Inc., © 2020 DuPont.